## RJ11, RJ12 and RJ45 plugs





## Technical parameters

10GBASE-T and lower (CAT6A) 1000BASE-T and lower (CAT5E and CAT6) 10BASE-T (CAT3)

RJ45, RJ12, RJ11 1000 cycles

50 μin gold (CAT5E, CAT6, CAT6A) 15 μin gold (CAT3)

AWG 28 - 22 FR according to UL94-0

-40 to +70°C -10 to +60°C

93 %

Product number	Type number	Description
11238907	KRJS45/6ASLD	RJ45 Plug Solarix CAT6A 8p8c Shielded for Solid Wire
11238905	KRJ45/6SLD	RJ45 Plug Solarix CAT6 8p8c Unshielded for Solid Wire
11238903	KRJ45/6	RJ45 Plug Solarix CAT6 8p8c Unshielded for Stranded Wire
11238904	KRJ45/6SH	RJ45 Plug Solarix CAT6 8p8c Shielded for Stranded Wire
11238805	KRJ45/5SLD	RJ45 Plug Solarix CAT5E 8p8c Unshielded for Solid Wire
11578804	KRJS45/5SLD	RJ45 Plug Solarix CAT5E 8p8c Shielded for Solid Wire
11238803	KRJ45/5	RJ45 Plug Solarix CAT5E 8p8c Unshielded for Stranded Wire
11238804	KRJ45/5SH	RJ45 Plug Solarix CAT5E 8p8c Shielded for Stranded Wire
11006600	KRJ12	RJ 12 Plug Solarix CAT3 ópóc Unshielded for Stranded Wire
11006400	KRJ11	RJ11 Plug Solarix CAT3 6p4c Unshielded for Stranded Wire









