

Signamax 065-9032 / 065-9042 is a user-friendly Indoor IP Camera, supporting both wired and wireless for easy installation. Whether for Home, Business or Public Facility surveillance, or just for fun, this IP Camera has the features the users need—all at an affordable price.

TRIPLE PLAY

Despite its compact size, 065-9032 / 065-9042 features two-way audio capability and excellent video quality—with VGA resolution at full 30 frames-per-second, either MPEG4 or M-JPEG compression, and video latency as short as 0.2 second or less. It supports both wired and wireless connection for easy installation. The video surveillance functions such as motion detection, alarm notifications...etc. are all included with the video monitoring software bundled with the IP camera—at no extra charge.

Signamax 065-9032 / 065-9042 IP Camera

FEATURES

- VGA Resolution (640x480) at 30 Frames-per-second
- Support MPEG-4 and M-JPEG Dual Video Streaming
- Support Mobile Phone 3GPP Live Video
- Support 802.11g Wireless and Wired 10/100 Base-T Ethernet
- Support Multiple Platform (Windows, Mac and Linux)
- Motion Detection & Email Alert



SPECIFICATIONS

VIDEO

Image Sensor: CMOS, 1/6" VGA Resolution
 Lens: F2.8 Fixed Focus, Effective Range: 0.2M to infinity
 Compression: MPEG-4/M-JPEG Dual Stream
 Resolution Support: 640x480, 320x240, 160x120
 Frame Rate: Up to 30 frame per second in VGA (640x480)
 Image Control: AWB, Brightness
 Video Options: Motion-Detection, Time Stamp, Text Overlay
 3GPP: 160x120@15fs, MPEG-4 for mobile phone viewing

AUDIO

Compression: G.711, G.726 ADPCM
 Microphone/Speaker: Bi-directional audio, built-in Mic and external Speaker
 Audio Option: On-Off control on web interface and Windows playback

NETWORK

Protocols: TCP/IP, SMTP, HTTP, DHCP, NTP, RTSP/RTP, UPnP

SOFTWARE

Operating System: Linux
 Management Interface: Windows Setup utility, Web based user interface
 Client Support: Web Browser, Windows Utility
 Security: Username and Password
 E-mail Notification: Triggered by motion detection
 Users: 5 simultaneous users

WIRELESS (065-9042)

Standard: IEEE 802.11b and 802.11g
 Operation Modes: Infrastructure/Ad-Hoc
 Range: Indoor: 50m
 Encryptions: WEP 64 Bits/128 Bits, WPA-PSK Personal, WPA2 Personal
 Frequency: 2.4~2.4835 GHz, DSSS
 Antenna: 2dbi, Detachable

HARDWARE

CPU: SC1100 SOC with Hardware MPEG-4/M-JPEG Codec
 Flash ROM: 4 Megabytes
 SDRAM: 32 Megabytes
 LAN: Ethernet 10/100BaseT
 LED Indicators: Power, Active, Network
 Connector: Ethernet RJ-45, Speaker out, DC Power, Reset button
 Power Adapter: 5V/1A, 100/240 VAC
 Certification: CE/FCC
 Dimensions (HxWxD): 96 x 90 x 36 mm (3.8 x 3.5 x 1.4")
 Weight: 131g (0.29 lb.) without stand, 256g (0.56 lb.) with stand

Signamax 065-9032 / 065-9042 IP Camera

PART NO.	DESCRIPTION
065-9032	Signamax IP camera MPEG4, 1/6" CMOS
065-9042	Signamax WiFi IP camera, MPEG4, 1/6" CMOS

