

SX108 and SX288 Wall Outlets CAT5E



SX288-5E-UTP-WH

2.5/5
Gbps

100
MHz

These wall-mount Solarix one-port and two-port outlets have an excellent performance and are offered in both unshielded and shielded versions. They easily exceed electrical parameters specified in the ANSI/TIA 568C.2, ISO/IEC 11801, and EN 50173 standards. Both T568A and T568B wiring configurations are supported on their 110 termination block. The SX108 and SX288 outlets come with red and blue port markers for each port allowing easy administration. The colour of the outlets is white.

Technical parameters

Supported protocols	2.5/5GBASE-T and lower	Conductor Size and Type	AWG 26 – 22, solid
Number of Ports	1 and 2x RJ45	Other Material	FR according to UL94-0
Life Cycle	750 plug insertions	Colour	White
Contact Material	50 µin gold	Dimensions	60 x 56 x 28 mm
IDC Block	110 8p8c	Storage Temperature	-40 to +70 °C
IDC Block Life Cycle	200 terminations	Operation Temperature	-10 to +60 °C
		Max. Humidity Operation	93%

Product number	Type number	Description
22161081	SX108-5E-UTP-WH	Surface Mount Outlet Solarix Category 5E UTP 1 x RJ45 White
22161080	SX108-5E-STP-WH	Surface Mount Outlet Solarix Category 5E STP 1 x RJ45 White
22162880	SX288-5E-UTP-WH	Surface Mount Outlet Solarix Category 5E UTP 2 x RJ45 White
22162881	SX288-5E-STP-WH	Surface Mount Outlet Solarix Category 5E STP 2 x RJ45 White



SX108-5E-UTP-WH



SX108-5E-STP-WH

