

Signamax 065-9033 / 065-9043 is an user-friendly Indoor Pan-and-Tilt IP Camera, supporting wired (065-9033) and wireless (065-9043) for easy installation. Whether for Home, Business or Public Facility surveillance, or just for fun, this IP Camera has the features the users need—all at an affordable price.

TRIPLE PLAY

Despite its compact size, 065-9033 / 065-9043 features motorized Pan-and-Tilt control, two-way audio capability and excellent video quality—with VGA resolution at full 30 frames-per-second, either MPEG4 or M-JPEG compression, and video latency as short as 0.2 second or less. It supports both wired and wireless connection for easy installation. The video surveillance functions such as motion detection, alarm notification...etc. are all included with the video monitoring software bundled with the IP camera—at no extra charge.

Signamax Compact Pan & Tilt IP Camera

FEATURES

- Remote Pan-and-Tilt, Digital Zoom IP Camera
- VGA Resolution (640x480) at 30 Frames-per-second
- Support both MPEG-4 and M-JPEG Dual Video
- Support Mobile Phone 3GPP Live Video
- Support 802.11g Wireless and Wired 10/100 Base-T Ethernet
- Support Multiple Platform (Windows, Mac and Linux)
- M-JPEG Server Push Live Video



SPECIFICATIONS

VIDEO

Image Sensor: CMOS, 1/4" VGA Resolution
 Lens: F2.0 Fixed Focus, Effective Range: 50cm to infinity
 Compression: MPEG-4/M-JPEG Dual Stream
 Resolution Support: 640x480, 320x240, 160x120
 Frame Rate: Up to 30 frame per second in VGA (640x480)
 Image Control: AWB, AGC, Contrast, Brightness
 Video Options: Motion-Detection, Time Stamp, Text Overlay
 3GPP: 160x120@15fs, MPEG-4 for mobile phone viewing

PAN/TILT

Pan Range: 126° (Left 63°~Right 63°) + 57° View Angle
 Tilt Range: 64° (Up 28°~down 36°) + 57 View Angle
 Driver: Micro Stepping Motors
 Preset Position: 10 Preset Positions, Support Patrol Mode
 Digital Zoom: 4x Digital Zoom

AUDIO

Compression: G.726 ADPCM
 Microphone/Speaker: Bi-directional audio, built-in Mic and external Speaker
 Audio Option: On-Off control on web interface and Windows playback

NETWORK

Protocols: TCP/IP, SMTP, HTTP, DHCP, NTP, RTSP/RTP, UPnP

SOFTWARE

Operating System: Linux
 Management Interface: Windows Setup utility, Web based user interface
 Client Support: Web Browser, Windows Utility
 Security: Username and Password
 E-mail Notification: Triggered by motion detection
 Users: 5 simultaneous users

WIRELESS (065-9043)

Standard: IEEE 802.11b and 802.11g
 Operation Modes: Infrastructure/Ad-Hoc
 Range: Indoor: 50m
 Encryptions: WEP 64 Bits/128 Bits, WPA-PSK
 Frequency: 2.4~2.4835 GHz, DSSS
 Antenna: 2dbi, Detachable

HARDWARE

CPU: SC1100 SOC w/ Hardware MPEG-4/M-JPEG Codec
 Flash ROM: 4 Megabytes
 SDRAM: 32 Megabytes
 LAN: Ethernet 10/100BaseT
 LED Indicators: Power, Active, Network
 Connector: Ethernet RJ-45, SPK, DC Power, Reset
 DI/DO: 1xDigital In and 1xDigital Out
 Power Adapter: 5V/2A, 100/240 VAC
 Certification: CE/FCC
 Dimensions (HxWxD): 146 x 96 x 78 mm (5.7 x 3.8 x 3.1")
 Weight: 318g (0.70 lb.) without stand, 422g (0.93 lb.) with stand

Signamax Compact Pan & Tilt IP Camera

PART NO.	DESCRIPTION
065-9033	Signamax IP camera, MPEG4, 1/4" CMOS
065-9043	Signamax WiFi IP camera, MPEG4, 1/4" CMOS